

Nano Engine Protect & Seal (NEPS)

Nano Engine Protect & Seal

Product properties

PRO-TEC Nano Engine Protect & Seal creates a highly active nano barrier in the oil which protects all the internal surfaces of engines and equipment such as oil system, manual gearboxes and differentials. Seals, o-rings and shaft seals are kept supple. Improved oil flow during cold start, smoother and quieter engine running, improved performance, extended life of equipment, and excellent "run dry" emergency properties

Area of application

Service product for use in the oil system of 4-stroke petrol and diesel engines. Applicable for common rail as well as pump injector fuel systems and recommended for engines with turbo charger, catalytic converter and DPF filters. Compatible with all engine oils.

Application

Add to oil system after each oil change. We recommend cleaning the oil system with PRO-TEC Engine Flush before use. Observe the maximum oil quantity! In power-steering systems, manual transmissions und differentials use at ratio 1:10.

Note: When using in vehicles with wet clutch, observe the manufacturer's instructions!

Consumption

375ml sufficient for 5 liters of oil. Mixing ratio: 1:15.

Reaction time

while engine is running

Technical data

Physical state: viscous

Colour: brown

Odour: mild

Flashpoint: > 100 °C

Density at 68 °F: 0.90 - 0.95 g/cm³

Water resistant

Viscosity / kinematic (at 104 °F): 17,2 mm²/s

Available sizes	Item no.	PU
375ml	P9201	28
1L	P9209	12
5L	P9202	4



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.