

Diesel Fuel Stabilizer (DFS)

Diesel Fuel Stabilizer

Product properties

Diesel Fuel Stabilizer is a high-activity product which improves the operational characteristics of all diesel fuels that have been stored for an extended period of time.

Benefits:

- prevents fuel aging
- reduces deposits and resination
- provides optimum lubrication in the whole fuel system
- condensing water is bound
- prevents corrosion
- reduces foaming when the fuel is filled in a tank
- optimized exhaust emissions
- protects the environment

Area of application

Perfectly suited for all diesel and diesel-biodiesel fuels.

Application

Adding the product of a lengthy storage period (1/2- 2 years) of diesel fuel.

Consumption

1 litre product per 1,000 litre fuel

Reaction time

While engine is running

Technical data

Physical state: liquid

Colour: brown

Odour: characteristic

Initial boiling point and boiling range: 200 - 210 °C

Flashpoint: > 60 °C

Lower explosion limit: > 0,6 Vol.-%

Upper explosion limit: > 7,0 Vol.-%

Ignition temperature: > 200 °C

Vapour pressure (at 68 °F): > 8 hPa

Density at 68 °F: ca. 0.81 g/cm³

Water resistant

Available sizes	Item no.	PU
1L	P1281	12



Our information is based on careful examination and may be considered as reliable. However, all information supplied is non-binding advise. No liability for any printing errors. Technical modifications and errors are exempted.